



## SG6 – CLERMONT W/ DOGGY BARS SLIDING GATE

### FRAME

50 x 50 x 3mm SHS Frame sides

50 x 100 x 3mm RHS Bottom Rail

- Extends 400mm further than gate width for motor racking to attach to
- Sliding Gate wheels insert into Bottom Rail
- Standard Wheel Holes = 90 x 43mm
- Heavy Duty Wheel Holes = 120 x 43mm
- Wheel hole placement = 1/5th of Gate width (edge of gate to centre of hole)

50 x 50 x 3mm extruded top rail with Guide Angle

- Extends 400mm past gate to slot into Guide Block

Mitred Top Corners

### DESIGN

16mm CHS (1.2mm) Vertical Tubes

100mm Tube Centres

83 x 8mm Round S Scroll

83 x 8mm Round Ring

### MATERIALS

6063 T6 Aluminium

All of our Sliding Gates are available in the **Interpon Powder Coating Colour Range**

**NB //** Surcharges & extended lead times may be incurred with non-standard colour choices

TITLE: **CLERMONT W/ DOGGY BARS SLIDING GATE**

DRAWING NO: **SG6**

CONTACT: [sales@oxworks.com.au](mailto:sales@oxworks.com.au)

[oxworks.com.au](http://oxworks.com.au) // 1300 336 237