


HIGHER CUSTOM PANELS - Custom panels 1500mm High and above will have an extra rail 1200mm down from the top of the panel. If you require the extra rail positioned elsewhere, please let our sales staff know at the time of quoting.




500


200mm

IN GROUND POST DETAIL

CORE DRILL POST DETAIL



FLANGED (ON SLAB) POST DETAIL





WELD DETAILS

# **OXWORKS**

#### STANDARD PANELS

2400 x 1200mm Panel - Powdercoated 38 x 25m x 1.6mm RHS 16mm CHS (1.2mm) Vertical Tubes Pattern may vary

#### FIXINGS

38 x 25mm Horizontal Fence Brackets 2 Hole - Single Lugged 3 x 12-14\*20 Self Tapping Tek Screws used per Fence Bracket

#### STANDARD GATES

970 x 1200mm Gate - Powdercoated 38 x 25mm Frame (Non-Mitred)

#### **ALUMINIUM POSTS**

50 x 1800 x 1.6mm In Ground Post 50 x 2100 x 1.6mm In Ground Post 50 x 1300 x 1.6mm Flanged Post 50 x 1600 x 1.6mm Flanged Post

### • In Ground Post 200 x 500/600mm Post Hole Hole filled with Post Mix Concrete

# Core Drilled Post Minimum 75mm x 100mm Core Drill Hole filled with MP60 Non-Shrink Bostik

- Flanged Post On Slab M10 x 75mm Glavanised Dyna Bolt
- Flanged Post On Timber 14 x 75mm Hex Head Batten Screw into Structural timber

#### **MATERIALS**

6063 T6 Aluminium - Powder Coated

All of our Garden Fencing styles are available in the Interpon Powder Coating Colour Range

NB: All measurements have a manufacturing tolerance of +/- 2mm

## TITLE: ALUMINIUM GARDEN FENCING AYR

CONTACT: sales@oxworks.com.au

oxworks.com.au 1300 336 237

